

DAFTAR GAMBAR

Gambar 2.1 : <i>VoLTE Network Architecture</i>	8
Gambar 2.2 : <i>IMS with the LTE Evolved Packet Core</i>	9
Gambar 2.3 : <i>E-Node B Architecture</i>	12
Gambar 2.4 : <i>EPC Architecture</i>	14
Gambar 2.5 : <i>IMS Architecture</i>	19
Gambar 3.1 : <i>Flowchart Single Site Verification Drive Test</i>	28
Gambar 3.2 : <i>Nemo Outdoor Operation Mode</i>	31
Gambar 3.3 : <i>Nemo Outdoor Voice Call Testing Concept</i>	32
Gambar 4.1 : <i>Lokasi Site Drive Test</i>	34
Gambar 4.2 : <i>PCI Plot Lokasi Drive Test</i>	35
Gambar 4.3 : <i>RSRP (Reference Signal Received Power)</i>	40
Gambar 4.4 : <i>SINR (Signal to Interference & Noise Ratio)</i>	41
Gambar 4.5 : <i>Average Throughput SSV</i>	42
Gambar 4.6 : <i>Overshooting Criteria</i>	43
Gambar 4.7 : <i>VoLTE Calls Setup Flow</i>	45
Gambar 4.8 : <i>VoLTE Signaling</i>	46
Gambar 4.9 : <i>EPS Attach for VoIP and Default Bearer Setup</i>	47
Gambar 4.10 : <i>SIP IMS Call Flow</i>	51
Gambar 4.11 : <i>ViLTE Signaling</i>	53
Gambar 4.12 : <i>Grafik VoLTE Jitter</i>	61