

DAFTAR GAMBAR

Gambar 2.1 PDF <i>gaussian</i> random variable	7
Gambar 2.2 Fluktuasi Receive Signal Strength [17]	7
Gambar 2.3 Jangkauan AP WLAN dengan pemodelan shadowing [18].....	11
Gambar 2.4 Perkiraan outage fungsi jarak jangkauan [18].....	12
Gambar 2.5 Distribusi nilai BLE RSSI [19]	13
Gambar 2.6 Efek dari Filter <i>gaussian</i> [16].....	14
Gambar 2.7 Pengolahan RSSI [15].....	15
Gambar 3.1 Diagram kerja penelitian.....	16
Gambar 3.2 Tampak atas denah lokasi pengukuran.....	18
Gambar 3.3 Pengukuran di titik 1 environment 1	18
Gambar 3.4 Pengukuran di titik 2 <i>environment</i> 2.....	19
Gambar 3.5 Denah tampak samping pengukuran envirotment 2.	19
Gambar 3.6 Pengukuran environment 2 titik 4	19
Gambar 3.7 Status BLE support di smart phone	20
Gambar 3.8 Pengaturan power TX -1 dBm	21
Gambar 3.9 Aktivasi advertise mode ON.....	22
Gambar 3.10 RX UUID xx91xx.....	22
Gambar 3.11 RSSI pada jarak mendekati 0.	23
Gambar 3.12 Contoh File.log hasil scan BLE dengan raspberry.	23
Gambar 4.1 Jumlah sample RSSI pada pengukuran <i>Environment</i> 1	24
Gambar 4.2 <i>Coverage area environment</i> 1.....	25
Gambar 4.3 Rata-rata RSSI <i>Environment</i> 1	26
Gambar 4.4 Jumlah sample RSSI pada pengukuran Environment 2.....	27

Gambar 4.5 Coverage area environment 2 untuk TX -9 dBm.	28
Gambar 4.6 Rata-rata RSSI Environment 2.	29
Gambar 4.7 Grafik RSSI Gaussian filter TX -20dBm titik 1.....	30
Gambar 4.8 RSSI sebelum dan sesudah gaussian filter environment 1.....	31
Gambar 4.9 Histrogram RSSI Gaussian filter TX -9 dBm titik 4.	32
Gambar 4.10 RSSI sebelum dan sesudah gaussian filter environment 2.....	33
Gambar 4.11 Grafik TX -20 titik 3 <i>environment</i> 1.....	36
Gambar 4.12 Akurasi distance environment 1.	37
Gambar 4.13 Akurasi distance environment 2.	39

