

## DAFTAR TABEL

|   |    |
|---|----|
| Tabel 2.1 Hasil percobaan terkait nilai jitter .....                  | 12 |
| Tabel 2.2 Tipe-tipe <i>frame</i> Profinet/Ethernet .....              | 15 |
| Tabel 2.3 Pengukuran <i>cycle time</i> .....                          | 20 |
| Tabel 3.1 Pengaturan alamat IP perangkat .....                        | 41 |
| Tabel 3.2 Tabel pengaturan <i>acquisition cycle</i> .....             | 42 |
| Tabel 3.3 Pengaturan tag HMI .....                                    | 44 |
| Tabel 4.1 Respon kontroler IM151-8 PN/DP dengan 1 tag pada HMI.....   | 50 |
| Tabel 4.2 Respon kontroler IM151-8 PN/DP dengan 2 tag pada HMI.....   | 50 |
| Tabel 4.3 Respon kontroler IM151-8 PN/DP dengan 3 tag pada HMI.....   | 51 |
| Tabel 4.4 Respon kontroler Simatic IPC427D dengan 1 tag pada HMI..... | 52 |
| Tabel 4.5 Respon kontroler Simatic IPC427D dengan 2 tag pada HMI..... | 52 |
| Tabel 4.6 Respon kontroler Simatic IPC427D dengan 3 tag pada HMI..... | 53 |
| Tabel 4.7 Perbandingan respon antar kontroler .....                   | 56 |

## DAFTAR SINGKATAN

|      |  |
|------|--|
| AC   | <i>Alternating Current</i>                         |
| AR   | <i>Application Relationship</i>                    |
| ARP  | <i>Address Resolution Protocol</i>                 |
| CAN  | <i>Controller Area Network</i>                     |
| CBA  | <i>Component Based Architecture</i>                |
| CP   | <i>Communication Processor</i>                     |
| CPPS | <i>Cyber Physical Production System</i>            |
| CPS  | <i>Cyber Physical System</i>                       |
| CPU  | <i>Central Processing Unit</i>                     |
| CR   | <i>Communication Relationship</i>                  |
| DDE  | <i>Dinamic Data Exchange</i>                       |
| DHCP | <i>Dinamic Host Configuration Protocol</i>         |
| DNS  | <i>Domain Name Service</i>                         |
| DP   | <i>Decentralized Periphery</i>                     |
| HMI  | <i>Human Machine Interface</i>                     |
| ID   | <i>Identification</i>                              |
| IM   | <i>Interface Module</i>                            |
| IO   | <i>Input Output</i>                                |
| IOT  | <i>Internet og Things</i>                          |
| IP   | <i>Internet Protocol</i>                           |
| IPC  | <i>Industrial Personal Computer</i>                |
| IRT  | <i>Isochronous Run Time</i>                        |
| LLDP | <i>Link Layer Discovery Protocol</i>               |
| MAC  | <i>Media Access Control address</i>                |
| NBNS | <i>Net BIOS Name Service</i>                       |
| OPC  | <i>Object Linking and Embedded Process Control</i> |
| PC   | <i>Personal Computer</i>                           |
| PI   | <i>Profibus International</i>                      |

|        |  |
|--------|--|
| PLC    | <i>Programmable Logic Controller</i>                     |
| PN     | <i>Profinet</i>  |
| RT     | <i>Run Time</i>  |
| SCADA  | <i>Supervisory Control And Data Acquisition</i>          |
| TCP    | <i>Transmission Control Protocol</i>                     |
| TI ICE | <i>Texas Instruments Industrial Communication Engine</i> |
| UDP    | <i>User Data Protocol</i>                                |
| WINS   | <i>Windows Name Service</i>                              |

